



Australian Government

Geoscience Australia

Monitoring for CO₂ storage

Andrew Barrett

CCS School

Chengdu, 14-17 October, 2013

cags

China Australia Geological Storage of CO₂

中澳二氧化碳地质封存



Introduction

- We need to be able to safely store carbon dioxide in the subsurface and be sure we know how it is behaving
- To do this we need to be able to monitor the behaviour



China Australia Geological Storage of CO₂

中澳二氧化碳地质封存



Monitoring

- Monitoring has a spatial dimension and a time dimension
- Spatial dimension
 - Sub-surface
 - Near surface
 - Atmosphere
- Time dimension
 - Prior to injection
 - During injection
 - Post-injection



China Australia Geological Storage of CO₂
中澳二氧化碳地质封存



What are we monitoring for?

- Ensure effective storage
 - Is the stored CO₂ behaving as predicted?
 - If it isn't, can we determine why?
- Understand the impact on the environment; both subsurface (aquifers) and above ground (ecosystem and atmosphere impacts)
 - Is the CO₂ leaking away from the storage formation?
 - Is the CO₂ leaking to the surface?
 - What is the rate of leakage?




China Australia Geological Storage of CO₂

中澳二氧化碳地质封存



Natural CO₂ leaks

- Mammoth Mountain, California
 - up to 300 tons/day CO₂
 - soil gas concentrations 20-95%



Source: <http://pubs.usgs.gov/fs/fs172-96/>



Natural CO₂ leaks

- Latera Caldera, Italy
- ~10 t/d natural CO₂ leak



Source: Andrew Feitz

cags

China Australia Geological Storage of CO₂
中澳二氧化碳地质封存



Natural CO₂ leaks

- Views of CO₂ bubbling up through stream



Source: Andrew Feitz

cags

China Australia Geological Storage of CO₂
中澳二氧化碳地质封存



CO₂ toxicity

- CO₂ seeps have proved to be harmful to humans
- Material Safety Data Sheets show 47,000 ppm (4.7%) in air is considered to be toxic to humans
- “Concentrations of 8-15% cause headache, nausea and vomiting which may lead to unconsciousness if not moved to open air and given oxygen”
(source: http://msds.chemalert.com/?id=21&file=0008659_001_001.pdf)
- Also harmful to the environment
 - Acidification of soils
 - Alteration of groundwater chemistry




China Australia Geological Storage of CO₂

中澳二氧化碳地质封存



Leakage pathways



Source: http://www.co2crc.com.au/images/imagelibrary/stor_diag/potential-escape-routes_media.jpg




China Australia Geological Storage of CO₂
 中澳二氧化碳地质封存



© CO2CRC

Why is baseline monitoring important?

- We need to establish the natural (starting) conditions in order to be able to detect changes that may be caused by leakage from our storage formation



China Australia Geological Storage of CO₂
中澳二氧化碳地质封存



Groundwater baseline monitoring

- Groundwater resources are critical as a source of water for much of Australia and China therefore we need to know if the resources are being affected by leaking/migrating CO₂
- What does the baseline look like?



Potential impacts on groundwater chemistry


- pH decrease (immediate)
- Weathering will lead to increased alkalinity/TDS
- Increase in major ions (Ca, Mg, Fe, K, Na, Al and Mn)
- Major concern is movement of saline water into freshwater aquifers
- Other concerns
 - Trace metals (esp. As, Pb, Ni, Cr)
 - Trace organic contaminants
 - Boron (agriculture)
 - Si and Br (water treatment plants)
- Note metal leaching not only related to direct contact with CO₂, could occur outside assigned storage area



China Australia Geological Storage of CO₂

中澳二氧化碳地质封存






Coreena Wallumbilla

Cadna-owie Hooray Bungil


Adori




Total Dissolved Solids mg/L




0 750 km



Hutton



Precipice



Clemantis

Salinity



China Australia Geological Storage of CO₂
 中澳二氧化碳地质封存



What to measure?

- **Essential: Field pH and total dissolved solids (salinity)/ Electrical conductivity**
- Lab pH can be quite different to actual (field) pH due to rapid equilibrium with atmosphere
- Field analysis (pH, redox, temperature, EC; also helpful is Fe^{2+})
- Cations (Na, Mg, Ca, K) and anions (Cl , SO_4 , HCO_3 , F)
- Trace metals and metalloids (e.g. Pb, As, Al, B, Ni, Mn, Hg, Sr, Rb)
- Isotopes useful for aquifer characterisation (e.g. d^2H , d^{18}O , d^{13}C , ^{14}C , ^{36}Cl , $^{87}\text{Sr}/^{86}\text{Sr}$) but analysis is expensive
- Trace organics if mobilisation of oil/condensate a concern (e.g. BTEX, naphthalene and total recoverable hydrocarbons)
- Analysis of exsolved gases including composition and isotopic d^2H and d^{13}C analysis (methane and CO_2)



China Australia Geological Storage of CO_2

中澳二氧化碳地质封存



How can we monitor the CO₂ plume?

Remote	Hyperspectral imaging INSAR
Surface	Conventional seismic surveys Vertical seismic profiles (VSP) Gravity surveys Some electromagnetic techniques
Subsurface - downhole	Saturation logging Cross-well electromagnetic Borehole gravity Pressure Thermal effects Cross-well seismic Fluid sampling (tracers)



China Australia Geological Storage of CO₂

中澳二氧化碳地质封存



What should an injection monitoring program look like?

- Clearly no “one size fits all”
- Program needs to be customised to the particular storage area
- Will be a combination of any or all of the techniques on the previous slide plus any we have yet to think of




China Australia Geological Storage of CO₂


中澳二氧化碳地质封存




Optical satellite remote sensing



• 4th September 1988



5th September 1994




1st April 2010

Source: <http://www.cagsinfo.net/pdfs/cags2-workshop1/5-1LinlinGe1.pdf>




Radar satellite remote sensing



4D seismic - Sleipner

Time-lapse seismic images of the Sleipner CO₂ plume – North-South inline through the plume (top), plan view of total reflection amplitude in the plume (bottom)



cags

Source: http://nora.nerc.ac.uk/9418/1/Sleipner_TLE_v7_revised.pdf

China Australia Geological Storage of CO₂

中澳二氧化碳地质封存



Gas isotopes in groundwater

Field collection of exsolved gases from groundwater for isotopic analysis useful for detecting small leaks in overlying aquifers




What would a leak look like?

- No reported CO₂ leaks from CO₂ storage sites
- Investigating possible leakage scenarios using:
 - known leaky wells
 - natural CO₂ leaks
 - simulated leaks from controlled release facilities



Ginninderra controlled release facility, Canberra



cags

China Australia Geological Storage of CO₂
中澳二氧化碳地质封存



Ginninderra - 0.1 t/d simulated CO₂ leak




cags

China Australia Geological Storage of CO₂
中澳二氧化碳地质封存



Ginninderra CO₂ hot spots



China Australia Geological Storage of CO₂
中澳二氧化碳地质封存



Leaks are 'patchy'

- Patchiness is a common theme from controlled release experiments (ZERT, Ginninderra, CO₂ Lab (Norway)) and natural CO₂ seeps
- CO₂ finds highest permeability pathways to the surface
- High fluxes over a small area, not low fluxes over large areas
- Patches of dead vegetation a good indicator
- What appears homogenous is not when it comes to leakage



China Australia Geological Storage of CO₂

中澳二氧化碳地质封存



How do we quantify a leak?

- Primary technique is soil flux measurements
- Atmospheric measurements
 - Eddy covariance
 - Single sensor
 - Sensor array
 - Integrated line measurements



China Australia Geological Storage of CO₂

中澳二氧化碳地质封存



Soil flux

- Quick and easy but laborious
- ~150 measurements per day
- Accuracy is ~ 15%
- Two different approaches:

semi-permanent collars




portable chamber




Source: Westsystems, 2012



Soil flux – integrate flux measurements for total emission



g/m²/d



0.1 t/d leak

cags

China Australia Geological Storage of CO₂
中澳二氧化碳地质封存



Atmospheric techniques – Eddy Covariance

- Measures the vertical flux over relatively small areas (e.g. $\sim 100 \times 100\text{m}$)
- Quantifying leaks requires lot of data processing
- Footprint not well defined
- Application to small leaks could violate EC assumptions




Atmospheric techniques - single sensor

- Quantifying leaks requires lot of data processing
- Need meteorological data
- Need to be downwind of leak
- Couple with modelling software
 - Backward Lagrangian Stochastic “bLS” model for short distances (e.g. Windtrax)
 - atmospheric transport models for greater distances (e.g. TAPM)
- Total flux quantification can be moderately accurate (e.g. typically 10-50%)



Atmospheric – integrated line measurements

- Line measurements (e.g. DIAL or TDL) could resolve emissions quicker and accurately when coupled to inverse models
- Tuneable Diode Laser (TDL) systems presently too insensitive for small CO₂ leaks



CO₂ DIAL system (Figures courtesy of Kevin Repasky, Montana State University)

China Australia Geological Storage of CO₂

中澳二氧化碳地质封存



Conclusions

- CO₂ leaks likely to be small and patchy
- Soil flux measurements easiest method for quantifying leaks
- Atmospheric tomography is very accurate but difficult and slow
- Integrated line measurements coupled to inverse modelling show promise for rapid quantification (e.g. within a day)
- But ... need to find the leak in the first place
soil flux and atmospheric techniques are primarily for quantification, not detection



China Australia Geological Storage of CO₂

中澳二氧化碳地质封存



Questions?



China Australia Geological Storage of CO₂
中澳二氧化碳地质封存



Phone: +61 2 6249 9111

Web: www.ga.gov.au

Email: feedback@ga.gov.au

Address: Cnr Jerrabomberra Avenue and Hindmarsh Drive, Symonston ACT 2609

Postal Address: GPO Box 378, Canberra ACT 2601



China Australia Geological Storage of CO₂

中澳二氧化碳地质封存

